


LED Filament ST21(4W/7W)

Description:

Efficacy: 120lm/W
 Life Time: 25,000 HR
 RoHS
 UL Certification

Replacement:

40W Incandescent Bulbs
 60W Incandescent Bulbs




Parameters:

Material: Glass
 Input Voltage: 120/220VAC; 50/60Hz
 CCT: 2700K/4000K/6000K
 CRI: >80

View Angle: 360°
 Power Supply: Non-Isolate Drive
 Weight: 55g
 Life: 25,000 hr

Part NO.	CCT	CRI	Lumen	Input Voltage	Wattage	PF	Base	Dim
BL.XXA04JLTA00U	2700K	80	450lm	90-135V/60Hz	4W	0.5	E26	NO
BL.XXA04JLTAD0U	2700K	80	450lm	120V/60Hz	4.5W	0.9	E26	YES
BL.XXB04JKTA000	2700K	80	450lm	176-264V/50Hz	4W	0.5	E27	NO
BL.XXB04JKTAD00	2700K	80	450lm	220-230V/50Hz	4.5W	0.7	E27	YES
BL.XXA07JLTC00U	2700K	80	800lm	90-135V/60Hz	7W	0.5	E26	NO
BL.XXA07JLTCD0U	2700K	80	800lm	120V/60Hz	7W	0.9	E26	YES
BL.XXB07JKTC000	2700K	80	800lm	176-264V/50Hz	7W	0.5	E27	NO
BL.XXB07JKTCD00	2700K	80	800lm	220-230V/50Hz	7W	0.7	E27	YES

Packing information:



Master carton size:450*370*370mm
 Net weight:3.3kg; Gross weight:7.2kg
 15 bulbs/middle carton, 4 middle cartons/master carton

Installation:

Connect to E26/E27 base

Note:

1. The input voltage is 120/220VAC
2. Turn power off when install the LED filament bulbs
3. Check the bulbs and make sure it's undamaged before installation
4. LED filament bulbs are not suitable for insulated places
5. LED filament bulbs are prohibited installed outdoor place



Description of Dimmer Matching

Our LED lights have been designed and worked with listed dimmers:

For 2W-5W

LEVITON:

R62-6674-P0W
 C22-6672-1LW
 R70-6631-1LW

LUTRON:

DV-600P-WH
 MACL-153MR-WH
 CT-600PR-WH

For >5W

LEVITON:

R62-6674-P0W
 R70-6631-1LW

LUTRON:

DV-600P-WH
 MACL-153MR-WH

Remark:

1. Mismatch dimmer may lead to poor lighting effect.
2. Dimming range:20%-80%.
3. For the items less than 3W, one dimmer has to be connected with more than 2pcs each time.